



EROAD

EROAD ETrack Oyster3

Compact device with exceptional battery life



A rugged GPS tracking device, the Oyster3 has been designed for monitoring non-powered assets where long battery life is required, without sacrificing the frequency of updates and performance. Its low power design means that 3 AA batteries can power the device for 5+ years. Compact in size and concealable, the Oyster3 fits seamlessly onto your equipment to help reduce outside tampering.

KEY FEATURES

- 5+ years battery life
- Theft Recovery - Switch to Recovery Mode in the case of theft or loss to activate real-time tracking for asset retrieval
- No wires to connect - quickly and easily install the Oyster3 on any asset
- High-precision GPS/GLONASS tracking device
- Tracks assets when they're on the move and enters sleep mode when stationary to save power
- Weatherproof and rugged IP65 housing - Oyster 3 can be mounted on assets that are exposed to rain, dust

IDEAL FOR

- Trailers
- Agriculture equipment & implements
- Containers
- Pumps/generators/hire equipment
- Skip bins
- Other non-powered assets





TECHNICAL SPECIFICATIONS

Connectivity

The Oyster3 is available in LTE-M

LTE-M	Supported LTE bands: LTE-M (Cat-M1): B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66
SIM Size & Access	Internal Nano 4FF SIM
Batteries	
User-Replaceable Batteries	3 x AA
Supported Battery Types	*Lithium (LiFeS2) *Lithium Thionyl Chloride (LTC) *Lithium or LTC recommended for best performance. Please dispose of Lithium batteries in a safe and responsible manner.
Battery Life	5+ years with a combination of movement and stationary location updates.
Location	
GNSS Module	Sony CXD5605
Constellation	Concurrent GPS, GLONASS, Galileo, QZSS
Tracking Sensitivity	-147 dBm cold start / -161 dBm hot start
GNSS Assistance	GNSS almanac and ephemeris data for greater sensitivity and position accuracy
Low Noise Amplifier	GPS signals are filtered and boosted by a SAW filter and low-noise amplifier (LNA) allowing operation where other units fail
Power	
Input Voltage	3.8-16V DC
Sleep Current	<10uA* *Average current in lowest power configuration
Safety	Reverse Polarity Protection
Mechanics / design	
Dimensions	108 x 86 x 31 mm (4.25 x 3.39 x 1.22")
Weight	173g
Housing	Ultra-Rugged IP65 Housing
IP Rating	IP65 rated housing ensures device can withstand fine dust, high-pressure spray, submersion for 30 mins in 1m of water, and extreme temperatures
Installation	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more. Stainless steel screws provided
Operating Temperature	-30°C to +60°C For operation in extreme temperatures use LTC Batteries

Cellular Antenna	Internal
GPS Antenna	Internal
3-Axis Accelerometer	3-Axis Accelerometer to detect movement
Diagnostic LED	Diagnostic LED indicates operation status
Flash Memory	Store records on device if asset is out of cellular coverage. These are uploaded automatically when device comes back into cellular coverage.
On-Board Speed and Heading	Current speed and heading is reported with each position update
Smarts	
Battery Life Monitoring	'Battery Low' and 'Battery Critical' alert levels
Intelligent Power Management	Early registration abort saves power when out of cellular coverage
Periodic or Movement-Based Tracking	Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
Preventative Maintenance*	Set reminders based on run hours to reduce maintenance and repair costs
Run Hour Monitoring	Capture run hours based on movement to understand and optimise asset utilisation
Sleep Mode	Stationary devices enter sleep mode until movement occurs to conserve battery life and optimise data usage
Theft Recovery	Switch to Recovery Mode in the case of theft or loss to activate real-time tracking for asset retrieval
Device management	
Device Management Platform	Manage and monitor, devices remotely from MyEROAD
Security	
Data Security	Military-level AES-256 Encryption from device to OEM Server to protect the integrity and confidentiality of telematics data. Data forwarded to third-party systems is sent via HTTPS for end-to-end security
Warranty	
Manufacturer's Warranty	Manufacturer's Warranty

* **Note:** Run hours are calculated on MyEROAD and require the Oyster 3 to have moved at least 250m from original position.

See www.eroad.com.au, or call **1800 437 623** for more information.